

## CLAIM AMENDMENTS

### IN THE CLAIMS

This listing of the claims will replace all prior versions, and listing, of claims in the application or previous response to office action:

1. **(Currently Amended)** A method for changing between a packet-oriented PTT session and a circuit-oriented telephone connection as two selectable communication connections between at least one first ~~connected~~-radio communication appliance and at least one second ~~connected~~-radio communication appliance in a radio communication system, the method comprising:

selecting and setting up a first of the two communication connections by at least one of the at least one ~~connected~~-radio communication appliance and at least one control unit in a radio network in the radio communication system; and

changing from the first communication connection, which has already been set up, to a second of the two communication connections under control of at least one of the radio communication appliance which is connected to the first communication connection and a first control unit in the radio network in the radio communication system which is connected to the first communication connection by activating the second communication connection while the first communication connection still exists,

wherein the first communication connection is cleared down and terminated after the second communication connection has been established.

2. (Original) The method as claimed in claim 1, wherein in the first radio communication appliance uses the first communication connection, which has already been set up, to send the second radio communication appliance at least one control signal which is used to notify the second radio communication appliance of a need for the first radio communication appliance to change from the first communication connection to the second communication connection.

3. (Original) The method as claimed in claim 1, wherein at least one of the first and the second radio communication appliance is connected to the first communication connection, which has already been set up, sends the first control unit which is responsible for the first communication connection at least one control signal which is used to notify the first control unit of a need for at least one the first and the second radio communication appliances to change from the first communication connection to the second communication connection.

4. (Original) The method as claimed in claim 1, wherein at least one of the first and the second radio communication appliance is connected to the first communication connection, which has already been set up, sends a second control unit which is responsible for the second communication connection, which needs to be set up, at least one control signal which is used to notify the control unit of a need for at least one of the first and the second radio communication appliances to change from the first communication connection to the second communication connection.

5. (Original) The method as claimed in claim 1, wherein the first control unit connected to the first communication connection, which has already been set up, sends a control signal relating to a need for at least one of the first and the second radio communication appliances to change to a second control unit which is responsible for activating and setting up the second communication connection.

6. (Original) The method as claimed in claim 2, wherein the at least one control signal has inserted into it at least one of:

at least one address parameters for at least one of the second radio communication appliance, connected to the second communication connection, to which the need to change is directed and the first radio communication appliance, connected to the first communication connection, from which the need to change issues; and

at least one identification parameter for distinguishing the first communication connection, which has already been set up, from the second communication connection, which needs to be set up.

7. (Original) The method as claimed in claim 6, wherein the at least one identification parameter in the control signal is used to associate the first communication connection, which has already been set up, with the second communication connection, which is yet to be set up, such that an explicit link is brought about between the first communication connection and the second communication connection.

8. **(Cancelled)**

9. (Original) The method as claimed in claim 1, wherein, after the second communication connection has been established, the second communication connection is set up and maintained in parallel with the first communication connection, which has already been set up.

10. (Original) The method as claimed in claim 1, wherein the control unit used for the packet-oriented PTT session is a PTT server.

11. (Original) The method as claimed in claim 1, wherein the control unit used for the circuit-oriented telephone connection is an MSC switching unit.

12. **(Currently Amended)** A radio communication appliance for use in a method for changing between a packet-oriented PTT session and a circuit-oriented telephone connection as two selectable communication connections between the radio communication appliance and at least one further radio communication appliance in a radio communication system, comprising a control unit wherein a first of the two communication connections is selected and set up by the control unit, and a change is made from the first communication connection, which has already been set up, to a second of the two communication connections under control of the control unit which is connected to the first communication connection by activating the second communication connection while the first communication connection still exists, wherein the first communication connection is cleared down and terminated after the second communication connection has been established.

13. **(Currently Amended)** A network component for use in a method for changing between a packet-oriented PTT session and a circuit-oriented telephone connection as two selectable telecommunication connections between at least one first connected radio communication appliance and at least one second connected radio communication appliance in a radio communication system, the network component comprising a control unit wherein a first of the two communication connections is selected and set up by the control unit in a radio network in the radio communication system, and a change is made from the first communication connection, which has already been set up, to a second of the two communication connections under control of the control unit in the radio network in the radio communication system which is connected to the first communication connection by activating the second communication connection while the first communication connection still exists, wherein the first communication connection is cleared down and terminated after the second communication connection has been established.

14. **(Currently Amended)** A radio communication system having a first group of network components for selecting and providing a packet-oriented PTT session and a second group of network components for selecting and providing a circuit-oriented telephone connection as two selectable communication connections between at least one first connected radio communication appliance and at least one second connected radio communication appliance in the radio communication system, comprising control units in each of the first and second groups of network components wherein a first of the two communication connections is selected and set up by one of the control units in a radio network in the radio communication system, and a change is made from the first communication connection, which has already been set up, to a second of the two communication connections under control of the control unit in the radio network in the radio communication system which is connected to the first communication connection by activating the second communication connection while the first communication connection still exists, wherein the first communication connection is cleared down and terminated after the second communication connection has been established.

15. (NEW) A method for changing between a packet-oriented PTT session and a circuit-oriented telephone connection as two selectable communication connections between at least one first radio communication device and at least one second radio communication device in a radio communication system, the method comprising:

selecting and setting up a first of the two communication connections by at least one of the at least one radio communication device and at least one control unit in a radio network in the radio communication system; and

changing from the first communication connection, which has already been set up, to a second of the two communication connections under control of at least one of the radio communication device which is connected to the first communication connection and a first control unit in the radio network in the radio communication system which is connected to the first communication connection by activating the second communication connection while the first communication connection still exists,

wherein in the first radio communication device uses the first communication connection, which has already been set up, to send the second radio communication device at least one control signal which is used to notify the second radio communication device of a need for the first radio communication device to change from the first communication connection to the second communication connection.

16. (NEW) The method as claimed in claim 15, wherein at least one of the first and the second radio communication appliance is connected to the first communication connection, which has already been set up, sends the first control unit which is responsible for the first communication connection at least one control signal which is used to notify the first control unit of a need for at least one the first and the second radio communication appliances to change from the first communication connection to the second communication connection.

17. (NEW) The method as claimed in claim 15, wherein at least one of the first and the second radio communication device is connected to the first communication connection, which has already been set up, sends a second control unit which is responsible

for the second communication connection, which needs to be set up, at least one control signal which is used to notify the control unit of a need for at least one of the first and the second radio communication devices to change from the first communication connection to the second communication connection.

18. (NEW) The method as claimed in claim 15, wherein the first control unit connected to the first communication connection, which has already been set up, sends a control signal relating to a need for at least one of the first and the second radio communication devices to change to a second control unit which is responsible for activating and setting up the second communication connection.

19. (NEW) The method as claimed in claim 15, wherein the at least one control signal has inserted into it at least one of:

at least one address parameters for at least one of the second radio communication device, connected to the second communication connection, to which the need to change is directed and the first radio communication device, connected to the first communication connection, from which the need to change issues; and

at least one identification parameter for distinguishing the first communication connection, which has already been set up, from the second communication connection, which needs to be set up.

20. (NEW) The method as claimed in claim 19, wherein the at least one identification parameter in the control signal is used to associate the first communication connection, which has already been set up, with the second communication connection, which is yet to be set up, such that an explicit link is brought about between the first communication connection and the second communication connection.

21. (NEW) The method as claimed in claim 15, wherein, after the second communication connection has been established, the second communication connection is set

up and maintained in parallel with the first communication connection, which has already been set up.

22. (NEW) The method as claimed in claim 15, wherein the control unit used for the packet-oriented PTT session is a PTT server.

23. (NEW) The method as claimed in claim 15, wherein the control unit used for the circuit-oriented telephone connection is an MSC switching unit.